

Technical Certificate

Size: 500 60R22.5 AGRO-G 155D



Tire Size	500/60R22.5
Pattern	AGRO-G
Version	STANDARD
PR	---
LI/SS	155D
TT/TL	TL
ECE Approval No	E4*106R00/19*1807*02
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	16.00
Alt. Rim Width	---
SW (mm) ± 2%	504
O.D (mm) ± 2%	1173.9
SLR (mm) ± 2%	528
RC (mm) ± 2.5%	3509
NSD (mm) ± 1	26.0
Wt. (kgs) ± 3%	92.93

Application

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressur e	Load Capacity kg				
					Speed km/h			Speed km/h				
		Free Rolling	Drive Wheel		Static	65		kpa	Static	25	30	40
500 60R22.5	---	155D	400	8910	3875	100	3920	2690	2575	2320	1705	
						120	4370	3000	2870	2580	1900	
						160	5170	3550	3390	3060	2250	
						200	5880	4040	3860	3480	2560	
						240	6595	4530	4330	3900	2870	
						280	7220	4960	4740	4270	3140	
						320	7750	5330	5090	4585	3370	
						360	8380	5755	5500	4950	3640	
							400	8910	6120	5850	5270	3875

中策橡胶(天津)有限公司
ZHONGCE RUBBER (TIANJIN) CO.,LTD.

王兴平

2024.1.10

