

AG-RADIAL



Field Protection



Durability



Self-Cleaning



IF/VF Technology



Comfort

- Guaranteed true running and driving comfort up to 50 km/h
- Wide contact area for up to 4000 working hours
- More and wider lugs in ground and extended wear compound for durability
- Excellent driving on and off-the-road
- Good self-cleaning abilities due to special angle lugs
- Round shoulders for superior ground protection



AG-RADIAL 70/75 Series

TRA: R-1W

| Tire Size | Load/Speed Index | TT/TL | Tread Depth mm | Rim | Outer Diameter mm | Section Width mm | Static Loaded Radius mm ±2.5% | Rolling Circumference mm ±2.5% | Inflation Pressure KPa | Load Capacity Kg | | | | | | | |
|-------------|------------------|-------|-------------------|-----------------|----------------------|---------------------|-------------------------------------|--------------------------------------|---------------------------|------------------|-------|------|------|------|------|------|------|
| | | | | | | | | | | Static | 10 | 20 | 25 | 30 | 40 | 50 | 65 |
| 360/70R24 | 122A8/122B | TL | 42.0 | 11.00 | 1135 | 354 | 518 | 3398 | 160 | 3450 | 2250 | 1845 | 1665 | 1605 | 1500 | 1500 | - |
| 380/70R24 | 125A8/125B | TL | 42.0 | 12.00 | 1198 | 384 | 533 | 3574 | 160 | 3795 | 2475 | 2030 | 1830 | 1765 | 1650 | 1650 | - |
| 420/70R24 | 130A8/130B | TL | 45.0 | 13.00 | 1231 | 426 | 563 | 3675 | 160 | 4370 | 2850 | 2340 | 2110 | 2030 | 1900 | 1900 | - |
| 480/70R24 | 138A8/138B | TL | 47.0 | 15.00 | 1314 | 488 | 580 | 3913 | 160 | 5430 | 3540 | 2900 | 2620 | 2525 | 2360 | 2360 | - |
| | 400 | | | | | | | | 10930 | 6890 | 5840 | 5040 | 4940 | 4750 | 4750 | - | |
| 620/75R26 | 166A8/166B | TL | 53.0 | DW20B | 1601 | 620 | 694 | - | 320 | 12190 | 7950 | 6520 | 5830 | 5670 | 5300 | 5300 | - |
| 360/70R28 | 125A8/125B | TL | 42.0 | 11.00 | 1258 | 356 | 566 | 3777 | 160 | 3795 | 2475 | 2030 | 1830 | 1765 | 1650 | 1650 | - |
| 380/70R28 | 127D | TL | 42.0 | 12.00 | 1304 | 382 | 589 | 3903 | 160 | 4025 | 2625 | 2150 | 2070 | 2010 | 1915 | 1840 | 1750 |
| 420/70R28 | 133A8/133B | TL | 45.0 | 13.00 | 1350 | 414 | 597 | 4044 | 160 | 4740 | 3090 | 2530 | 2290 | 2200 | 2060 | 2060 | - |
| 480/70R28 | 140A8/140B | TL | 47.0 | 15.00 | 1431 | 477 | 643 | 4279 | 160 | 5750 | 3750 | 3075 | 2775 | 2675 | 2500 | 2500 | - |
| 600/70R28 | 157D | TL | 51.0 | DW18L | 1551 | 591 | - | - | 240 | 9490 | 6190 | 5070 | 4890 | 4740 | 4520 | 4330 | 4125 |
| VF600/70R28 | 168D | TL | 51.0 | DW20B | 1536 | 612 | - | - | 280 | 12880 | 7110 | 6050 | 5935 | 5820 | 5600 | 5600 | 5600 |
| 420/70R30 | 134A8/134B | TL | 45.0 | 13.00 | 1384 | 422 | 615 | 4153 | 160 | 4875 | 3180 | 2610 | 2350 | 2270 | 2120 | 2120 | - |
| 480/70R30 | 141A8/141B | TL | 47.0 | 15.00 | 1463 | 480 | 653 | 4382 | 160 | 5920 | 3860 | 3170 | 2860 | 2755 | 2575 | 2575 | - |
| 520/70R30 | 145A8/145B | TL | 48.0 | 16.00 | 1528 | 522 | 692 | 4572 | 160 | 6670 | 4350 | 3570 | 3220 | 3100 | 2900 | 2900 | - |
| | 240 | | | | | | | | 7935 | 5175 | 4240 | 3830 | 3690 | 3450 | 3450 | - | |
| 600/70R30 | 152A8/152B | TL | 51.0 | 20.00 | 1610 | 586 | 716 | 4804 | 160 | 8165 | 5325 | 4370 | 3940 | 3800 | 3550 | 3550 | - |
| | 160 | | | | | | | | 8165 | 5325 | 4370 | 4210 | 4085 | 3875 | 3730 | 3550 | - |
| VF600/70R30 | 170A8/170B | TL | 51.0 | DW20B, DW21B | 1610 | 586 | 716 | 4804 | 240 | 13800 | 6600 | 6240 | 6180 | 6120 | 6000 | 6000 | - |
| 710/75R32 | 177A8/177B | TL | 56.0 | DW23B | 1872 | 736 | - | - | 320 | 16790 | 10950 | 8980 | 8980 | 7810 | 7300 | 7300 | - |