

Technical Certificate

Size: 710/45R22.5 AGRO GRIP 165D



Tire Size	710/45R22.5
Pattern	AGRO GRIP
Version	STANDARD
PR	---
LI/SS	165D
TT/TL	TL
ECE Approval No	E4*106R00/19*2923*03
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	24.00
Alt. Rim Width	---
SW (mm) $\pm$ 2%	720
O.D (mm) $\pm$ 2%	1200
SLR (mm) $\pm$ 2%	538
RC (mm) $\pm$ 2.5%	3607
NSD (mm) $\pm$ 1	25.0
Wt. (kgs) $\pm$ 3%	137.77

Application

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressure	Load Capacity kg				
					Speed km/h			Speed km/h				
		Free Rolling	Drive Wheel		Static	65	kpa	Static	25	30	40	65
710/45R22.5	-	165D	400	11845	5150	100	5210	3580	3420	3080	2265	
						120	5800	3990	3810	3430	2520	
						160	6870	4720	4510	4060	2990	
						200	7820	5370	5130	4620	3400	
						240	8765	6020	5755	5180	3810	
						280	9590	6590	6300	5670	4170	
						320	10305	7080	6765	6090	4480	
						360	11130	7650	7310	6580	4840	
						400	11845	8140	7780	7000	5150	

中策橡胶(天津)有限公司
ZHONGCE RUBBER (TIANJIN) CO.,LTD.

张平

2024.1.10