



Technical data

AGRI KING																	
Tire Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius	Rolling Circumference	Inflation Pressure	Load Capacity kg							
			mm		mm	mm	mm±2.5%	mm±2.5%		kPa	Speed km/h						
											Static	10	20	25	30	40	50
VF600/60R28	157D	TL	48	DW20B	1426	585	-	-	60	5320	2545	2405	2380	2360	2315	2315	2315
									80	6105	2920	2760	2730	2708	2655	2655	2655
									120	7795	3730	3525	3490	3460	3390	3390	3390
									140	8635	4130	3905	3868	3832	3755	3755	3755
									160	9480	4540	4290	4250	4210	4125	4125	4125
VF540/65R30	158D	TL	48	DW20B	1469	562	-	-	60	5010	2395	2260	2240	2225	2180	2180	2180
									80	5750	2745	2595	2570	2550	2500	2500	2500
									120	7335	3510	3320	3280	3260	3190	3190	3190
									140	8115	3880	3670	3630	3600	3530	3530	3530
									160	8910	4260	4030	3990	3950	3875	3875	3875
VF600/60R30	158D	TL	48	DW20B	1482	580	-	-	60	5500	2628	2485	2460	2435	2390	2390	2390
									80	6305	3015	2850	2820	2792	2740	2740	2740
									120	8045	3845	3630	3600	3562	3495	3495	3495
									140	8905	4257	4025	3988	3945	3870	3870	3870
									160	9780	4675	4420	4380	4335	4250	4250	4250