



Technical data

AGRI KING																	
Tire Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius	Rolling Circumference	Inflation Pressure	Load Capacity kg							
			mm		mm	mm	mm±2.5%	mm±2.5%	kPa	Speed km/h							
										Static	10	20	25	30	40	50	65
IF650/60R34	165D	TL	58	DW23B	1648	656	-	-	80	-	3210	3015	2960	2910	2800	2800	2800
									120	-	4130	3875	3805	3740	3595	3595	3595
									140	-	4600	4300	4225	4150	4000	4000	4000
									160	-	5030	4725	4640	4555	4375	4375	4375
									200	-	5480	5150	5055	4960	4750	4750	4750
									240	-	5920	5562	5459	5355	5150	5150	5150
VF710/60R38	171D	TL	56	DW25B	1784	692	783	-	60	7955	3800	3595	3555	3520	3455	3455	3455
									80	9120	4355	4120	4075	4030	3960	3960	3960
									120	11632	5560	5260	5200	5150	5055	5055	5055
									140	12880	6160	5825	5765	5700	5600	5600	5600
									160	14145	6765	6400	6335	6270	6150	6150	6150