



Technical data

AGRI KING																	
Tire Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius	Rolling Circumference	Inflation Pressure	Load Capacity kg							
			mm		mm	mm	mm±2.5%	mm±2.5%		kPa	Speed km/h						
											Static	10	20	25	30	40	50
VF650/65R42	174D	TL	58	DW23B	1915	664	796	-	60	7715	3680	3480	3445	3420	3355	3355	3355
									80	9210	4400	4160	4120	4085	4005	4005	4005
									120	11520	5510	5205	5158	5110	5010	5010	5010
									140	12670	6065	5730	5675	5622	5510	5510	5510
									160	13810	6615	6250	6190	6130	6010	6010	6010
									200	15400	7370	6970	6900	6830	6700	6700	6700
VF710/60R42	173D	TL	58	DW25B	1896	688	839	-	60	8405	4021	3800	3760	3725	3655	3655	3655
									80	9635	4605	4353	4315	4270	4190	4190	4190
									120	9990	4780	4520	4475	4430	4345	4345	4345
									140	13600	6510	6155	6095	6035	5918	5918	5918
									160	14950	7150	6760	6695	6630	6500	6500	6500

Aug,5th.2024