

DEFENDER



Field Protection



Reduced Soil Compaction

- Row crop tires with rounded shoulders for every kind of cultivation, harvesting and spraying operation
- Minimum damage to crops even in narrow spaced plantations
- Strong radial casing for optimum ground pressure distribution and low ground compaction lowers damage to soil and increases crop yield



DEFENDER

TRA: R-1

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ± 2.5%	Rolling Circumference mm ± 2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
230/95R32 (9.5R32)	128D	TL	33.0	7.00, W7, W8	1240	236	585	3742	400	Static	10	20	25	30	40	50	65
270/95R32 (11.2R32)	136D	TL	35.0	9.00, W9, W8, W10	1319	284	620	3975	400	5150	3360	2755	2655	2575	2450	2350	2240
230/95R36 (9.5R36)	128D	TL	33.0	7.00, W7, W8	1345	229	636	4078	360	4140	2700	2210	2130	2070	1970	1890	1800
270/95R36 (11.2R36)	137D 139D	TL	35.0	9.00, W9, W8, W10	1422	283	663	4291	360 400	5290 5590	3450 3645	2830 2990	2725 2880	2645 2795	2520 2660	2415 2550	2300 2430
270/95R38 (11.2R38)	140D	TL	35.0	9.00, W9, W8, W10	1474	285	691	4450	400	5750	3750	3075	2960	2875	2740	2625	2500
230/95R40 (9.5R40)	135D	TL	33.0	7.00, W7, W8	1454	228	662	4395	400	5010	3270	2680	2585	2505	2385	2290	2180
230/95R42 (9.5R42)	133D	TL	33.0	7.00, W7, W8	1497	228	684	4527	400	4740	3090	2530	2440	2370	2255	2165	2060
270/95R42 (11.2R42)	140D	TL	35.0	9.00, W9, W8, W10	1580	283	744	4774	360	5750	3750	3075	2960	2875	2740	2625	2500
320/80R42	141D	TL	35.0	10.00, W10, W9, W11	1567	315	730	4771	320	5920	3860	3165	3050	2960	2820	2705	2575
230/95R44 (9.5R44)	134D	TL	33.0	7.00, W7, W8	1547	229	735	4679	400	4875	3180	2610	2510	2440	2320	2230	2120
270/95R44 (11.2R44)	142D	TL	35.0	9.00, W9, W8, W10	1627	279	768	4917	400	6095	3975	3260	3140	3050	2900	2780	2650
270/95R46 (11.2R46)	143D	TL	35.0	9.00, W9, W8, W10	1677	282	798	5066	400	6270	4090	3350	3230	3135	2985	2860	2725
300/95R46 (12.4R46)	148D	TL	37.0	9.00, W9, W10, W11	1732	305	815	5233	400	7245	4725	3875	3730	3620	3450	3310	3150
320/90R46 (12.4R46)	148D	TL	37.0	10.00, W10, W9, W11	1737	315	810	5248	360	7245	4725	3875	3730	3620	3450	3310	3150
340/85R46	150D	TL	41.0	11.00, W12, W11	1770	352	835	5345	360	7705	5025	4120	3970	3850	3670	3515	3350
230/95R48 (9.5R48)	136D	TL	33.0	7.00, W7, W8	1647	230	780	4984	400	5150	3360	2755	2654	2575	2450	2350	2240
270/95R48 (11.2R48)	144D	TL	35.0	9.00, W9, W8, W10	1734	286	821	5243	400	6440	4200	3440	3320	3220	3065	2940	2800

Tire Size	Load/Speed Index	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Static Loaded Radius mm ± 2.5%	Rolling Circumference mm ± 2.5%	Inflation Pressure KPa	Load Capacity Kg							
										Speed Km/h							
340/85R48	152D	TL	37.0	11.00, W12, W11	1803	339	850	5463	400	8165	5325	4370	4210	4080	3890	3730	3550
300/95R52 (12.4R52)	151D	TL	37.0	9.00, W9, W10, W11	1889	305	895	5712	400	7935	5175	4240	4090	3965	3780	3620	3450
270/95R54 (11.2R54)	146D/149A8	TL	35.0	W9	1880	277	889	5718	400	6900	4500	3690	3330	3210	3250	3000	3000