

FOREST LEADER



- Optimised tread design and radial structure provide excellent traction.
- Equipped with high load capacity.
- Low rolling resistance reduces fuel consumption.
- Compared with traditional forestry tires, it provides smoother driving response and more comfortable feeling.
- Adaptable for heavy forestry use tractors and other forestry machines.

Size	Load/Speed Index	TT/TL	Rim	TRA Code	Tread Depth (mm)	Overall Diameter (mm)	Section Width (mm)	Inflation Pressure (KPa)	Load Capacity (Kg)		
									Static (Km/h)	40 (Km/h)	50 (Km/h)
*540/65R28	152A8/149B	TL	18.00	LS-2	49	1410	550	160	6050	2240	2060
								200	6750	2500	2300
								240	7560	2800	2575
								280	8300	3075	2800
								320	9045	3350	3075
								360	9585	3550	3250
*600/60R28	159A8/156B	TL	20.00	LS-2	49	1430	590	160	7360	2725	2500
								200	8505	3150	2900
								240	9585	3550	3250
								280	10460	3875	3550
								320	11140	4125	3750
								360	11810	4375	4000
*650/65R38	171A8/168B	TL	23.00	LS-2	50	1805	650	160	10460	3875	3550
								200	11810	4375	4000
								240	13160	4875	4500
								280	14310	5300	4875
								320	15660	5800	5300
								360	16605	6150	5600

*With Steel Belt