

SEWP

SUPER EXTRA WOODLAND PREMIUM



- This Tire has premium wide and deep "herringbone" tread bars with 45° angle, a flat profile plus kevlar or steel belt protection on sidewall and tread, so you end up with this ultimate forestry Tire designed to stand up to the most tough working conditions. This Tire is your only choice.

SEWP								TRA: LS-1	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Load Capacity		
							Inflation kPa	Speed 30km/h Load kg	
18.4-38	16	TT/TL	41.0	W16A DD16 W15L	1763	457	300	4375	
*18.4-38	16	TT/TL	41.0	W16A DD16 W15L	1763	457	300	4375	

SEWP								TRA: LS-2	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Load Capacity		
							Inflation kPa	Speed 30km/h Load kg	
16.9-30	16	TT	53.0	W15L DW15A W14L DW14A	1488	414	310	3250	
*16.9-30	16	TT	53.0	W15L DW15A W14L DW14A	1488	414	310	3250	
18.4-26	16	TT/TL	50.5	DW16A	1450	455	280	3450	
*18.4-26	16	TT/TL	50.5	DW16A	1450	455	280	3450	
18.4-30	14	TL	50.5	DW16A	1557	483	240	3350	
	16	TT/TL					280	3650	
*18.4-30	16	TT/TL	50.5	DW16A	1557	483	280	3650	
18.4-34	14	TL	51.0	DW16A DW15A	1664	447	240	3550	
	16	TT/TL					280	3875	
*18.4-34	16	TT/TL	51.0	DW16A DW15A	1664	447	280	3875	
20.5-25	16	TL	50.5	17.00/2.0 (1.7)	1450	427	225	4500	
	20	TL					275	5000	
20.8-38	16	TT/TL	50.5	W18A DD18 DW18A	1834	528	250	4750	
*20.8-38	16	TT/TL	50.5	W18A DD18 DW18A	1834	528	250	4750	
23.1-26	16	TT/TL	63.5	DW20B	1628	584	240	4500	
*23.1-26	16	TT/TL	63.5	DW20B	1628	584	240	4500	
	20	TT/TL					280	4875	

SEWP							TRA: LS-2	
Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Load Capacity	
							Inflation kPa	Speed 30km/h Load kg
24.5-32	16	TT/TL	59.5	DH21 DH21H	1806	587	210	5000
	20	TT					280	6000
*24.5-32	16	TT/TL	59.5	DH21 DH21H	1806	587	210	5000
	20	TT/TL					280	6000
	24	TL					340	6700
28L-26	16	TT	57.0	DW25B	1676	683	210	4750
	18	TT					220	4875
30.5L-32	16	TT/TL	66.5	DH27 DH27H	1844	732	170	5300
	20	TT/TL					210	6000
*30.5L-32	16	TT	66.5	DH27 DH27H	1844	732	170	5300
	20	TT/TL					210	6000
	26	TT					280	15700

Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Load Capacity	
							Inflation kPa	Speed 40km/h Load kg
*380/85-24	14	TL	47.5	W12	1260	380	240	2300
*380/85-28	14	TL	47.5	W12	1365	380	240	2430
*420/85-28	14	TL	53.5	W15L W14L	1432	428	240	2800

*: With Steel Belt