

DEFENDER

DEFENDER																	
Tyre Size	Load/Speed Index	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Static Loaded Radius	Rolling Circumference	Inflation Pressure	Load Capacity kg							
			mm		mm	mm	mm±2.5%	kPa		Speed km/h							
										Static	10	20	25	30	40	50	65
230/95R32 (9.5R32)	128A8/128B	TL	33,0	7.00, W7, W8	1240	236	585	3742	400	4140	2700	2210	2000	1930	1800	1800	-
270/95R32 (11.2R32)	136A8/136B	TL	35,0	9.00, W9, W8, W10	1319	284	620	3975	400	5150	3360	2755	2485	2400	2240	2240	-
	136D								400	5150	3360	2755	2655	2575	2450	2350	2240
230/95R36 (9.5R36)	128A8/128B	TL	33,0	7.00, W7, W8	1345	229	636	4078	360	4140	2700	2210	2000	1930	1800	1800	-
270/95R36 (11.2R36)	137A8/137B	TL	35,0	9.00, W9, W8, W10	1422	283	663	4291	360	5290	3450	2830	2550	2460	2300	2300	-
	139A8/139B								400	5590	3645	2990	2700	2600	2430	2430	-
270/95R38 (11.2R38)	140A8/140B	TL	35,0	9.00, W9, W8, W10	1474	285	691	4450	400	5750	3750	3075	2775	2675	2500	2500	-
	140D								400	5750	3750	3075	2960	2875	2740	2625	2500
230/95R40 (9.5R40)	135A8/135B	TL	33,0	7.00, W7, W8	1454	228	662	4395	400	5010	3270	2680	2420	2330	2180	2180	-
230/95R42 (9.5R42)	133A8/133B	TL	33,0	7.00, W7, W8	1497	228	684	4527	400	4740	3090	2530	2290	2200	2060	2060	-
270/95R42 (11.2R42)	140A8/140B	TL	35,0	9.00, W9, W8, W10	1580	283	744	4774	360	5750	3750	3075	2775	2675	2500	2500	-
	140D								360	5750	3750	3075	2960	2875	2740	2625	2500
320/80R42	141A8/141B	TL	35,0	10.00, W10, W9, W11	1567	315	730	4771	320	5920	3860	3170	2860	2755	2575	2575	-
230/95R44 (9.5R44)	134A8/134B	TL	33,0	7.00, W7, W8	1547	229	735	4679	400	4875	3180	2610	2350	2268	2120	2120	-
	134D								400	4875	3180	2610	2510	2440	2320	2230	2120
270/95R44 (11.2R44)	142A8/142B	TL	35,0	9.00, W9, W8, W10	1627	279	768	4917	400	6095	3975	3260	2940	2835	2650	2650	-
	142D								400	6095	3975	3260	3140	3050	2900	2780	2650
270/95R46 (11.2R46)	143A8/143B	TL	35,0	9.00, W9, W8, W10	1677	282	798	5066	400	6270	4090	3350	3025	2915	2725	2725	-
300/95R46 (12.4R46)	148A8/148B	TL	37,0	9.00, W9, W10, W11	1732	305	815	5233	400	7245	4725	3875	3500	3370	3150	3150	-
	148D								400	7245	4725	3875	3730	3620	3450	3310	3150
320/90R46 (12.4R46)	148A8/148B	TL	37,0	10.00, W10, W9, W11	1737	315	810	5248	360	7245	4725	3875	3500	3370	3150	3150	-
340/85R46	150A8/150B	TL	41,0	11.00, W12, W11	1770	352	835	5345	360	7705	5025	4120	3720	3585	3350	3350	-
230/95R48 (9.5R48)	136A8/136B	TL	33,0	7.00, W7, W8	1647	230	780	4984	400	5150	3360	2755	2485	2396	2240	2240	-
	136D								400	5150	3360	2755	2654	2575	2450	2350	2240
270/95R48 (11.2R48)	144A8/144B	TL	35,0	9.00, W9, W8, W10	1734	286	821	5243	400	6440	4200	3440	3110	3000	2800	2800	-
	144D								400	6440	4200	3440	3320	3220	3065	2940	2800
340/85R48	152A8/152B	TL	37,0	11.00, W12, W11	1803	339	850	5463	400	8165	5325	4370	3940	3800	3550	3550	-
	152D								400	8165	5325	4370	4210	4080	3890	3730	3550
300/95R52 (12.4R52)	151A8/151B	TL	37,0	9.00, W9, W10, W11	1889	305	895	5712	400	7935	5175	4240	3830	3690	3450	3450	-
270/95R54 (11.2R54)	146D/149A8	TL	35,0	W9	1880	277	/	/	400	6900	4500	3690	3330	3210	3250	3000	3000