

FIELD MASTER

COMING
SOON



Field
Protection



Reduced Soil
Compaction



Excellent
Traction



Self
Cleaning

- The herringbone pattern design optimizes the angle of the tread pattern to provide good self-cleaning and traction.
- The grounding marks are enlarged on both sides of the tire to reduce localized pressure on the tire, reducing compaction on the soil and improving crop protection.
- Super-high price/performance ratio, especially suitable for tractor operation and short-distance transportation.



FIELD MASTER

TRA: R-1

Tire Size	P. R.	TT/TL	Tread Depth mm	Rim	Outer Diameter mm	Section Width mm	Inflation Pressure KPa	Load Capacity Speed 30 km/h Kg
8.3-24	6	TT	29	W7	995	210	240	800
9.5-24	8	TT	32	W8	1045	234	280	1120
9.5-28	8	TT	32	W8	1134	234	280	1180
11.2-24	8	TT	34	W10	1105	285	240	1250
11.2-28	8	TT	34	W10	1205	285	240	1320
12.4-24	8	TT	35	W11	1160	315	230	1450
NEW 12.4-28	8	TT	35	W11	1260	315	230	1550
12.4-32	8	TT	35	W11	1360	315	230	1600
12.4-36	8	TT	35	W11	1465	315	230	1700
NEW 13.6-24	8	TT	36	W12	1210	345	200	1550
13.6-28	8	TT	36	W12	1310	345	200	1650
13.6-36	8	TT	36	W12	1515	345	200	1850
13.6-38	8	TT	36	W12	1565	345	200	1950
14.9-24	8	TT	37	W13	1265	378	180	1800
14.9-28	8	TT	37	W13	1315	378	180	1900
15.5-38	8	TT	36	W14L	1570	395	180	2060
16.9-30	8	TT	38	W15L	1485	430	170	2300
NEW 16.9-34	8	TT	38	W15L	1585	430	170	2430

FIELD MASTER

Tire Size	P. R.	TT/TL	Tread Depth	Rim	Outer Diameter	Section Width	Inflation Pressure	Load Capacity
			mm		mm			Speed 30 km/h Kg
16.9-38	8	TT	38	W15L	1685	430	170	2575
	10						140	2430
18.4-30	12	TT	40	W16L	1550	467	180	2900
	12						230	3250
18.4-34	10	TT	40	W16L	1655	467	180	3000
	12						230	3450
18.4-38	12	TT/TL	40	W16A	1755	467	230	3650
	16	TL					290	4375
20.8-38	8	TT	41	W18L	1835	528	130	3150
	12	TT/TL					200	4000
23.1-26	12	TT/TL	41	DW20B	1605	587	170	3650
	16	TL					230	4375
	18	TL					260	4625
23.1-30	8	TT/TL	41	DW20B	1705	587	110	3000
	12						170	3875
24.5-32	12	TL	42	DW21B	1805	622	170	4375
	14						200	4875