



- This Tire has premium wide and deep "herringbone" tread bars with 45° angle, a flat profile plus kevlar or steel belt protection on sidewall and tread, so you end up with this ultimate forestry Tire designed to stand up to the most tough working conditions. This Tire is your only choice.

| SEWP      |       |       |                   |      |       |      |       |                         | TRA: LS-2              |               |         |
|-----------|-------|-------|-------------------|------|-------|------|-------|-------------------------|------------------------|---------------|---------|
| Tire Size | P. R. | TT/TL | Tread Depth<br>mm | Rim  |       |      |       | Outer<br>Diameter<br>mm | Section<br>Width<br>mm | Load Capacity |         |
|           |       |       |                   |      |       |      |       |                         |                        | Speed 30km/h  |         |
|           |       |       |                   |      |       |      |       |                         |                        | Inflation kPa | Load kg |
| *16.9-30  | 16    | TT    | 53.0              | W15L | DW15A | W14L | DW14A | 1488                    | 414                    | 310           | 3250    |

| Tire Size<br>Designation | Tread<br>Pattern | Ply<br>Rating | Load Index<br>Speed<br>Symbol |   | Inflation<br>Pressure |     | Load Capacity (kg) (lbs.) |       |      |      |      |      |      |      |
|--------------------------|------------------|---------------|-------------------------------|---|-----------------------|-----|---------------------------|-------|------|------|------|------|------|------|
|                          |                  |               |                               |   |                       |     | Speed (km/h) (mph)        |       |      |      |      |      |      |      |
|                          |                  |               |                               |   | kPa                   | psi | 0*                        | 10*   | 15   | 20   | 25   | 30   | 40   | km/h |
|                          |                  |               |                               |   |                       |     | 0*                        | 5*    | 10   | 12.5 | 15   | 20   | 25   | mph  |
| 16.9-30    LS            | SEWP             | 16PR          | 149A6                         | / | 310                   | 45  | 8775                      | 4550  | 3900 | 3740 | 3575 | 3250 | 2925 | kg   |
|                          |                  |               |                               |   |                       |     | 19350                     | 10030 | 8600 | 8250 | 7880 | 7150 | 6450 | lbs. |