



- This Tire has premium wide and deep "herringbone" tread bars with 45° angle, a flat profile plus kevlar or steel belt protection on sidewall and tread, so you end up with this ultimate forestry Tire designed to stand up to the most tough working conditions. This Tire is your only choice.

tyre size	P.R.	load/speed index	type		tread depth	standard rim	overall width	overall diameter	static loaded radius	rolling circumference	load capacity at 40km/h	inflation pressure
			TT	TL	mm	inch	mm	mm	mm	mm	kg	kpa
23.1-26	16	160A6/172A2	Δ	Δ	63.5	DW20A	587	1628	730	4818	4050	240
	20	163A6/175A2	Δ	X							4385	280

Tire Size Designation		Tread Pattern	Ply Rating	Load Index Speed Symbol		Inflation Pressure		Load Capacity (kg) (lbs.)							
								Speed (km/h) (mph)							
								0*	10*	15	20	25	30	40	km/h
						kPa	psi	0*	5*	10	12,5	15	20	25	mph
23.1-26	LS	SEWP	16PR	160A6	172A2	240	35	12150	6300	5400	5175	4950	4500	4050	kg
								26790	13900	11900	11410	10910	9900	8930	lbs.
23.1-26	LS	SEWP	20PR	163A6	175A2	280	40	13160	6900	5850	5610	5360	4875	4390	kg
								29010	15200	12900	12370	11820	10700	9680	lbs.