

Technical Certificate

Size: 400/70R20BRS(ST)149A8149BTL



Tire Size	400/70R20
Pattern	BRS(ST)
Version	STANDARD
PR	---
LI/SS	149A8149B
TT/TL	TL
ECE Approval No	E4*106R00/19*2483*02
Tire Segment	Agricultural
TRA Code	R-4
Rec Rim Width	13
Alt. Rim Width	---
SW (mm) ± 2%	408
O.D (mm) ± 2%	1072
SLR (mm) ± 2%	476
RC (mm) ± 2.5%	3203
NSD (mm) ± 1	33.0
Wt. (kgs) ± 3%	66.43

Application

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressur e	Load Capacity kg					
					Speed km/h	Speed km/h		Speed km/h					
		Free Rolling	Drive Wheel					Static	50	kpa	Static	10	25
400/70R20	---	149A8149B		400	7475	3250	160	4335	2355	2000	1960	1885	1885
							200	4930	2680	2270	2230	2145	2145
							240	5530	3005	2550	2500	2405	2405
							280	6055	3290	2790	2740	2630	2630
							320	6500	3530	3000	2940	2830	2830
							360	7030	3820	3240	3180	3055	3055
							400	7475	4060	3445	3380	3250	3250

中策橡胶(天津)有限公司
 ZHONGCE RUBBER (TIANJIN) CO.,LTD.

2024.2.21

