

Technical Certificate

Size: 560/45R22.5 RIDE KING(SB) 152D



Tire Size	560/45R22.5 IMP
Pattern	RIDE KING(SB)
Version	STANDARD
PR	---
LI/SS	152D
TT/TL	TL
ECE Approval No	E4*106R00/19*1940*03
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	AG16.00
Alt. Rim Width	---
SW (mm) ± 2%	535
O.D (mm) ± 2%	1059.3
SLR (mm) ± 2%	480
RC (mm) ± 2.5%	3190
NSD (mm) ± 1	25.0
Wt. (kgs) ± 3%	96.11

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg							
					Speed km/h							
		Free Rolling	Drive Wheel		Static	10	20	25	30	40	50	65
560/45R22.5 IMP	---	152D		160	4760	3725	3415	3270	3100	2815	2500	2070
				200	5425	4250	3890	3730	3540	3210	2860	2360
				240	6050	4730	4340	5160	3950	3580	3180	2630
				280	6620	5180	4750	4550	4320	3920	3480	2880
				320	7176	5620	5150	4930	4680	4240	3780	3120
				360	7680	6010	5510	5280	5010	4540	4040	3340
				400	8165	6390	5860	5610	5360	4830	4295	3550

中策橡胶(天津)有限公司
ZHONGCE RUBBER (TIANJIN) CO., LTD.

2024.03.20

