

Technical Certificate

Size: 560/60R22.5 AGRO GRIP(ST) 164D



Tire Size	560/60R22.5
Pattern	AGRO GRIP(ST)
Version	STANDARD
PR	---
LI/SS	164D
TT/TL	TL
ECE Approval No	E4*106R00/19*3287*02
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	16.00
Alt. Rim Width	---
SW (mm) ± 2%	558
O.D (mm) ± 2%	1240.1
SLR (mm) ± 2%	559
RC (mm) ± 2.5%	3767
NSD (mm) ± 1	25.0
Wt. (kgs) ± 3%	115.44

Application

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressur e	Load Capacity kg					
					Speed km/h			Speed km/h					
		Free Rolling	Drive Wheel		Static	65	kpa	Static	25	30	40	65	
560/60R22.5	---	164D		400	11500	5000	100	5060	3475	3320	2990	2200	
							120	5635	3870	3700	3330	2450	
							150	6440	4420	4230	3810	2800	
							160	6670	4580	4380	3940	2900	
							200	7590	5210	4980	4490	3300	
							240	8510	5845	5590	5030	3700	
							280	9315	6400	6115	5510	4050	
							320	10005	6870	6570	5915	4350	
							360	10810	7425	7100	6390	4700	
							400	11500	7900	7550	6800	5000	

中策橡胶(天津)有限公司
ZHONGCE RUBBER (TIANJIN) CO., LTD.

张平

2024.1.10