

## Technical Certificate

Size: 560/60R22.5 IMPAGRO-GRIP161DTL



|                 |                      |
|-----------------|----------------------|
| Tire Size       | 560/60R22.5 IMP      |
| Pattern         | AGRO-GRIP            |
| Version         | STANDARD             |
| PR              | ---                  |
| LI/SS           | 161D                 |
| TT/TL           | TL                   |
| ECE Approval No | E4*106R00/19*1810*03 |
| Tire Segment    | Agricultural         |
| TRA Code        | ---                  |
| Rec Rim Width   | AG16.00              |
| Alt. Rim Width  | ---                  |
| SW (mm) ± 2%    | 567                  |
| O.D (mm) ± 2%   | 1260.2               |
| SLR (mm) ± 2%   | 559                  |
| RC (mm) ± 2.5%  | 3767                 |
| NSD (mm) ± 1    | 25.0                 |
| Wt. (kgs) ± 3%  | 115.55               |

### Application

| Tyre Size       | PR  | Load Index<br>Speed Symbol |                | Inflation<br>Pressure<br>kpa | Load Capacity<br>kg |     | Inflation<br>Pressur<br>e | Load Capacity kg |      |      |      |      |      |      |    |
|-----------------|-----|----------------------------|----------------|------------------------------|---------------------|-----|---------------------------|------------------|------|------|------|------|------|------|----|
|                 |     |                            |                |                              | Speed km/h          |     |                           | Speed km/h       |      |      |      |      |      |      |    |
|                 |     | Free<br>Rolling            | Drive<br>Wheel |                              | Static              | 65  | kpa                       | Static           | 10   | 25   | 30   | 40   | 50   | 60   | 65 |
| 560/60R22.5 IMP | --- | 161D                       | 400            | 10640                        | 4625                | 100 | 4680                      | 3660             | 3215 | 3070 | 2770 | 2460 | 2180 | 2035 |    |
|                 |     |                            |                |                              |                     | 120 | 5210                      | 4080             | 3580 | 3420 | 3080 | 2740 | 2425 | 2265 |    |
|                 |     |                            |                |                              |                     | 160 | 6170                      | 4830             | 4240 | 4050 | 3650 | 3245 | 2870 | 2680 |    |
|                 |     |                            |                |                              |                     | 200 | 7020                      | 5495             | 4820 | 4610 | 4150 | 3690 | 3265 | 3050 |    |
|                 |     |                            |                |                              |                     | 240 | 7870                      | 6160             | 5410 | 5170 | 4655 | 4140 | 3660 | 3420 |    |
|                 |     |                            |                |                              |                     | 280 | 8615                      | 6740             | 5920 | 5660 | 5095 | 4530 | 4010 | 3745 |    |
|                 |     |                            |                |                              |                     | 320 | 9255                      | 7240             | 6360 | 6075 | 5470 | 4870 | 4305 | 4020 |    |
|                 |     |                            |                |                              |                     | 360 | 10000                     | 7825             | 6870 | 6565 | 5910 | 5260 | 4650 | 4350 |    |
|                 |     |                            |                |                              |                     | 400 | 10640                     | 8325             | 7310 | 6980 | 6290 | 5595 | 4950 | 4625 |    |

中策橡胶(天津)有限公司  
ZHONGCE RUBBER (TIANJIN) CO.,LTD.

张平

2024.3.14