

Technical Certificate

Size: 600/50R22.5 AGRO GRIP(SB) 167D



Tire Size	600/50R22.5
Pattern	AGRO GRIP(SB)
Version	STANDARD
PR	---
LI/SS	167D
TT/TL	TL
ECE Approval No	E4*106R00/16*3675*00
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	20.00
Alt. Rim Width	---
SW (mm) ± 2%	608
O.D (mm) ± 2%	1168.0
SLR (mm) ± 2%	522
RC (mm) ± 2.5%	3507
NSD (mm) ± 1	25.0
Wt. (kgs) ± 3%	117.54

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressur e	Load Capacity kg							
					Speed km/h			Speed km/h							
		Free Rolling	Drive Wheel		Static	65	kpa	Static	10	25	30	40	50	60	65
600/50R22.5	---	167D		500	12535	5450	100	4890	3825	3360	3210	2890	2570	2270	2125
							120	5390	4220	3700	3540	3190	2835	2510	2340
							160	6390	5000	4390	4200	3780	3360	2970	2780
							200	7270	5690	4990	4770	4300	3825	3380	3160
							240	8150	6380	5600	5350	4820	4285	3790	3540
							280	8900	6965	6110	5840	5260	4680	4140	3870
							320	9650	7550	6630	6340	5710	5080	4490	4200
							360	10280	8040	7060	6750	6080	5410	4780	4470
							400	10905	8535	7490	7160	6450	5740	5070	4740
							450	11780	9220	8090	7735	6970	6200	5480	5120
							500	12535	9810	8610	8230	7410	6595	5830	5450

中策橡胶（天津）有限公司

ZHONGCE RUBBER (TIANJIN) CO.,LTD.

Signature

2024.3.14

