

Technical Certificate

Size: 600/50R22.5 IMPAGRO-GRIP159DTL



Tire Size	600/50R22.5 IMP
Pattern	AGRO-GRIP
Version	STANDARD
PR	---
LI/SS	159D
TT/TL	TL
ECE Approval No	E4*106R00/20*2199*02
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	AG20.00
Alt. Rim Width	---
SW (mm) ± 2%	605
O.D (mm) ± 2%	1167.2
SLR (mm) ± 2%	522
RC (mm) ± 2.5%	3507
NSD (mm) ± 1	25.0
Wt. (kgs) ± 3%	103.2

Application

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressur e	Load Capacity kg							
		Free Rolling	Drive Wheel		Speed km/h			Speed km/h							
					Static	65		kpa	Static	10	25	30	40	50	60
600/50R22.5 IMP	---	159D	400	10060	4375	100	4430	3465	3040	2910	2620	2330	2060	1925	
						120	4930	3860	3390	3240	2915	2590	2290	2140	
						150	5635	4410	3870	3700	3330	2965	2620	2450	
						160	5835	4570	4010	3830	3450	3070	2715	2540	
						200	6640	5200	4560	4360	3930	3490	3090	2890	
						240	7445	5830	5115	4890	4400	3920	3460	3240	
						280	8150	6380	5600	5350	4820	4290	3790	3540	
						320	8750	6850	6010	5750	5180	4605	4070	3805	
						360	9460	7400	6500	6210	5590	4975	4400	4110	
400	10060	7875	6910	6605	5950	5290	4680	4375							

中策橡胶(天津)有限公司
ZHONGCE RUBBER (TIANJIN) CO.,LTD.

2024.3.14

