

Technical Certificate

Size: 600/55R26.5 AGRO GRIP 165D



Tire Size	600/55R26.5
Pattern	AGRO GRIP
Version	STANDARD
PR	---
LI/SS	165D
TT/TL	TL
ECE Approval No	E4*106R00/19*1809*03
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	20.00
Alt. Rim Width	---
SW (mm) $\pm$ 2%	613
O.D (mm) $\pm$ 2%	1316.2
SLR (mm) $\pm$ 2%	586
RC (mm) $\pm$ 2.5%	3966
NSD (mm) $\pm$ 1	25.0
Wt. (kgs) $\pm$ 3%	135.1

Application

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressur e	Load Capacity kg				
					Speed km/h			Speed km/h				
		Free Rolling	Drive Wheel		Static	65	kpa	Static	25	30	40	65
600/55R26.5	---	165D		400	11845	5150	100	5210	3580	3420	3080	2265
							120	5800	3990	3810	3430	2520
							160	6870	4720	4510	4060	2990
							200	7820	5370	5130	4620	3400
							240	8765	6020	5755	5180	3810
							280	9590	6590	6300	5670	4170
							320	10305	7080	6765	6090	4480
							360	11130	7650	7310	6580	4840
							400	11845	8140	7780	7000	5150

中策橡胶(天津)有限公司
ZHONGCE RUBBER (TIANJIN) CO.,LTD.

2024.1.10

王平