

### Technical Certificate

Size: 600/55R26.5 RIDE KING(SB) 165D



Tire Size	600/55R26.5 IMP
Pattern	RIDE KING(SB)
Version	STANDARD
PR	---
LI/SS	165D
TT/TL	TL
ECE Approval No	E4*106R00/19*1809*03
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	AG 20.00
Alt. Rim Width	---
SW (mm) ± 2%	606
O.D (mm) ± 2%	1315.6
SLR (mm) ± 2%	600
RC (mm) ± 2.5%	3947
NSD (mm) ± 1	25.0
Wt. (kgs) ± 3%	135.28

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg							
		Free Rolling	Drive Wheel		Speed km/h							
					Static	10	20	25	30	40	50	65
600/55R26.5 IMP	---	165D		160	6900	5400	4950	4740	4500	4080	3630	3000
				200	7890	6170	5660	5420	5150	4660	4150	3430
				240	8790	6880	6300	6040	5730	5200	4620	3820
				280	9610	7520	6900	6600	6270	5680	5060	4180
				320	10400	8140	7460	7140	6780	6150	5470	4520
				360	11130	8710	7990	7650	7260	6580	5860	4840
				400	11845	9270	8500	8140	7780	7000	6230	5150

中策橡胶(天津)有限公司  
ZHONGCE RUBBER (TIANJIN) CO.,LTD.

2024.03.20

