

Technical Certificate

Size: 650/50R22.5 IMPAGRO-GRIP163DTL



Tire Size	650/50R22.5 IMP
Pattern	AGRO-GRIP
Version	STANDARD
PR	---
LI/SS	163D
TT/TL	TL
ECE Approval No	E4*106R00/19*1936*02
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	AG20.00
Alt. Rim Width	---
SW (mm) ± 2%	648
O.D (mm) ± 2%	1204.2
SLR (mm) ± 2%	532
RC (mm) ± 2.5%	3619
NSD (mm) ± 1	25.0
Wt. (kgs) ± 3%	126.09

Application

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressur e	Load Capacity kg							
					Speed km/h			Speed km/h							
		Free Rolling	Drive Wheel		Static	65	kpa	Static	10	25	30	40	50	60	65
															
650/50R22.5 IMP	---	163D		400	11210	4875	100	4930	3860	3390	3240	2920	2595	2295	2145
							120	5490	4300	3770	3610	3250	2890	2555	2390
							160	6500	5090	4470	4270	3845	3420	3025	2830
							200	7400	5790	5080	4860	4375	3890	3440	3220
							240	8300	6490	5700	5450	4905	4365	3860	3610
							280	9080	7110	6240	5960	5370	4780	4225	3950
							320	9755	7630	6700	6400	5770	5130	4540	4240
							360	10540	8250	7240	6920	6230	5545	4900	4580
							400	11210	8775	7700	7360	6630	5900	5215	4875

中策橡胶（天津）有限公司
ZHONGCE RUBBER (TIANJIN) CO.,LTD.

王平

2024.3.6