

Technical Certificate

Size: 650/55R26.5 AGRO-GST 178D



Tire Size	650/55R26.5
Pattern	AGRO GRIP(ST)
Version	STANDARD
PR	---
LI/SS	178D
TT/TL	TL
ECE Approval No	E4*106R00/19*2924*02
Tire Segment	Agricultural
TRA Code	
Rec Rim Width	20.00
Alt. Rim Width	---
SW (mm) ± 2%	645
O.D (mm) ± 2%	1364.0
SLR (mm) ± 2%	625
RC (mm) ± 2.5%	4196
NSD (mm) ± 1	25.0
Wt. (kgs) ± 3%	180.99

Application

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressur e	Load Capacity kg				
					Static	65		Speed km/h				
		Free Rolling	Drive Wheel					Static	25	30	40	65
650/55R26.5	---	178D		500	17250	7500	100	6730	4620	4420	3980	2925
							120	7420	5095	4870	4385	3225
							160	8800	6040	5775	5200	3825
							200	10005	6870	6570	5915	4350
							240	11210	7700	7360	6630	4875
							280	12250	8410	8040	7240	5325
							320	13280	9125	8720	7850	5775
							360	14145	9720	9290	8360	6150
							400	15010	10310	9850	8870	6525
500	17250	11850	11325	10200	7500							

中策橡胶(天津)有限公司
 ZHONGCE RUBBER (TIANJIN) CO.,LTD.

2024.1.10

