

Technical Certificate

Size: 710/50R26.5 IMPAGRO-GRIP170DTL



Tire Size	710/50R26.5 IMP
Pattern	AGRO-GRIP(SB)
Version	STANDARD
PR	---
LI/SS	170D
TT/TL	TL
ECE Approval No	E4*106R00/19*2163*03
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	REC AG20.00 and ALT AG24.00
Alt. Rim Width	---
SW (mm) ± 2%	728
O.D (mm) ± 2%	1365.9
SLR (mm) ± 2%	613
RC (mm) ± 2.5%	4113
NSD (mm) ± 1	25.0
Wt. (kgs) ± 3%	204.21

Application

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressur e	Load Capacity kg								
					Speed km/h			Speed km/h								
		Free Rolling	Drive Wheel		Static	65		kpa	Static	10	25	30	40	50	60	65
																
710/50R26.5 IMP	---	170D		400	13800	6000	100	6070	4750	4170	3985	3590	3190	2825	2640	
							120	6760	5290	4645	4440	4000	3560	3145	2940	
							160	8000	6260	5500	5255	4730	4210	3720	3480	
							200	9110	7130	6260	5980	5385	4790	4240	3960	
							240	10210	7990	7015	6700	6040	5370	4750	4440	
							280	11180	8750	7680	7340	6610	5880	5200	4860	
							320	12005	9395	8250	7880	7100	6315	5585	5220	
							360	12970	10150	8910	8515	7670	6820	6035	5640	
							400	13800	10800	9480	9060	8160	7260	6420	6000	

中策橡胶(天津)有限公司
ZHONGCE RUBBER (TIANJIN) CO.,LTD.

张平

2024.3.6