

Technical Certificate

Size: 750/60R30.5 R-KINGST 181D



Tire Size	750/60R30.5
Pattern	RIDE KING(ST)
Version	STANDARD
PR	---
LI/SS	181D
TT/TL	TL
ECE Approval No	E4*106R00/19*2347*02
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	24.00
Alt. Rim Width	---
SW (mm) ± 2%	773
O.D (mm) ± 2%	1652
SLR (mm) ± 2%	738
RC (mm) ± 2.5%	4992
NSD (mm) ± 1	25.0
Wt. (kgs) ± 3%	239.8

Application

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg		Inflation Pressur e	Load Capacity kg							
					Speed km/h			Speed km/h							
		Free Rolling	Drive Wheel		Static	65		kpa	Static	10	20	25	30	40	50
750/60R30.5	-	181D		400	18975	8250	160	11090	8680	7950	7620	7230	6560	5830	4820
							200	12630	9880	9060	8670	8240	7470	6640	5490
							240	14080	11020	10100	9670	9180	8320	7400	6120
							280	15390	12040	11040	10570	10040	9100	8100	6690
							320	16650	13030	11950	11440	10860	9850	8760	7240
							360	17850	13970	12800	12260	11640	10550	9390	7760
400	18975	14850	13610	13035	12460	11220	9980	8250							

中策橡胶(天津)有限公司
 ZHONGCE RUBBER (TIANJIN) CO.,LTD.

2024.1.16

