

Technical Certificate

Size: 800/45R26.5 RIDE KING(SB)174DTL



Tire Size	800/45R26.5 IMP
Pattern	RIDE KING(SB)
Version	STANDARD
PR	---
LI/SS	174D
TT/TL	TL
ECE Approval No	E4*106R00/19*5253*00
Tire Segment	Agricultural
TRA Code	---
Rec Rim Width	AG28.00
Alt. Rim Width	---
SW (mm) ± 2%	775
O.D (mm) ± 2%	1383.7
SLR (mm) ± 2%	625
RC (mm) ± 2.5%	4110
NSD (mm) ± 1	25.0
Wt. (kgs) ± 3%	185.93

Tyre Size	PR	Load Index Speed Symbol		Inflation Pressure kpa	Load Capacity kg							
					Speed km/h							
		Free Rolling	Drive Wheel		Static	10	20	25	30	40	50	65
800 45R26.5	---	174D		160	8990	7040	6450	6180	5865	5320	4730	3910
				200	10260	8030	7360	7050	6690	6070	5400	4460
				240	11430	8950	8200	7850	7460	6760	6010	4970
				280	12490	9770	8960	8580	8150	7380	6570	5430
				320	13520	10580	9700	9290	8820	8000	7110	5880
				360	14490	11340	10395	9950	9450	8570	7620	6300
				400	15410	12060	11050	10590	10100	9110	8110	6700

中策橡胶(天津)有限公司
ZHONGCE RUBBER (TIANJIN) CO.,LTD.

保平

2024.3.20