

SUPER EXTRA WOODLAND

SEWP | SUPER EXTRA WOODLAND PREMIUM

[TRA Code: LS-2] Steel Belt



- Highly durable, sturdy and robust construction
- 45° angle premium „herringbone“ tread bars
- low profile
- rim flange protector
- protected sidewall against snags and branches
- steel belt protection on sidewall and tread
- designed to stand the most tough working conditions
- the ultimate forestry tyre

This tyre has premium wide and deep „herringbone“ tread bars with 45°angle, a low profile plus steel belt protection on sidewall and tread. The Super Extra Woodland is the ultimate forestry tyre, designed to withstand the toughest working environments and your best choice!

SUPER EXTRA WOODLAND

SEWP

	tyre size	P.R.	load/speed index	type		tread depth	standard rim	overall width	overall diameter	static loaded radius	rolling circumference	load capacity at 40km/h	inflation pressure
				TT	TL								
						mm	inch	mm	mm	mm	mm	kg	kpa
NEW	380/85-24 [14.9-24]	14	137A8/134B	X	Δ	47.5	W12	380	1260	587	3784	2300	240
	20.5-25	16	N/A	Δ	Δ	50.5	17.00	427	1450	647	4321	4000	225
		20		Δ	Δ							4500	275
	460/85-26 [18.4-26]	14	N/A	Δ	X	50.5	DW16A	455	1450	647	4321	2810	240
		16	147A8/154A2	Δ	X							3075	280
NEW	23.1-26	16	160A6/172A2	Δ	Δ	63.5	DW20A	587	1628	730	4818	4050	240
		20	163A6/175A2	Δ	X							4385	280
	28L-26	16	N/A	Δ	Δ	57	DW25A	683	1676	748	4960	4275	210
		20		Δ	Δ							5040	280
NEW	380/85-28 [14.9-28]	14	139A8/136B	X	Δ	47.5	W12	380	1365	636	4097	2430	240
NEW	420/85-28 [16.9-28]	14	144A8/141B	X	Δ	53.5	DW15L	428	1432	670	4297	2800	240
	16.9-30	14	N/A	Δ	Δ	53	W15L W14L DW14A	414	1488	664	4440	2700	280
		16		Δ	Δ							2920	310
	18.4-30	14	N/A	Δ	Δ	50.5	DW16A	483	1557	695	4680	2990	240
		16		Δ	Δ							3275	280
	24.5-32	16	N/A	Δ	Δ	59.5	DH21 DH21H	587	1806	806	5388	4500	210
		20		Δ	Δ							5360	280
	30.5L-32	16	N/A	Δ	Δ	66.5	DH27 DH27H	732	1844	823	5495	4770	170
		20		Δ	Δ							5400	210
	18.4-34	14	N/A	Δ	Δ	51	DW16A	447	1664	743	4959	3200	240
		16		Δ	Δ							3490	280
	18.4-38*	16	N/A	Δ	Δ	41	W16A W15L	457	1763	787	5254	3900	300
	20.8-38	16	N/A	Δ	Δ	50.5	W18A DW18A	528	1834	819	5465	4280	260

Δ = available X = not available

*TRA CODE: LS-1

