

500/55 – 20 IMP 150A8 TL FLOTATION+

EAN CODE: **8714692174865**
 SKU CODE: **LB505520508FLLA00**
 ECE NUMBER: **E4-106R-000403**



Recommended rim width:	16.00
Nominal Tyre Pressure:	240 kpa
Section Width:	515 mm
Outer Diameter:	1060 mm
Static Loaded Radius:	475 mm
Rolling Circumference:	3160 mm
SRI:	500
Tread depth:	14 mm

Speed (km/h)	Pressure (bar)								
	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	3,00
	LLV								HLV
10	2500	2810	3120	3440	3760	4060	4380	4680	5620
25	2130	2390	2660	2920	3180	3460	3720	3980	4780
30	2000	2250	2500	2750	3000	3260	3500	3760	4500
40			2230	2460	2680	2900	3120	3340	4020
50					2410	2610	2810	3020	3620

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- LLV (Low Load Variation)
- HLV (High Load Variation)