

600/65 R 28 147D TL TRAXION XXL

EAN CODE: **8714692326943**
 SKU CODE: **LB60652847DTXLA00**
 ECE NUMBER: **E4-106R-001097**



Recommended rim width:	DW18L
Permitted rim width:	W18L
Nominal Tyre Pressure:	160 kpa
Section Width:	595 mm
Outer Diameter:	1480 mm
Static Loaded Radius:	670 mm
Rolling Circumference:	4405 mm
SRI:	700
Tread depth:	50 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	2575	2920	3280	3625	3985	4260	4500	4775
10H	2135	2480	2815	3105	3355	3535		
25	2200	2555	2900	3200	3455	3645		
30	2135	2480	2815	3105	3355	3535		
40		2360	2680	2955	3190	3365		
50		2260	2570	2835	3060	3230		
65			2450	2700	2915	3075		
70			2230	2460	2655	2800		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.