

710/70 R 38 166D TL TRAXION XXL

EAN CODE: **8714692326974**
 SKU CODE: **LB71703866DTXLA00**
 ECE NUMBER: **E4-106R-001100**



Recommended rim width:	DW23B
Permitted rim width:	DW25B
Nominal Tyre Pressure:	160 kpa
Section Width:	730 mm
Outer Diameter:	1930 mm
Static Loaded Radius:	870 mm
Rolling Circumference:	5760 mm
SRI:	925
Tread depth:	58 mm

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	4370	4965	5570	6165	6770	7255	7670	8130
10H	3630	4210	4785	5355	5755	6095		
25	3740	4340	4935	5520	5930	6280		
30	3630	4210	4785	5355	5755	6095		
40		4010	4560	5100	5480	5805		
50		3845	4370	4890	5255	5565		
60			4160	4660	5005	5300		
70			3790	4240	4555	4825		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES