

710/70 R 38 171D TL TRAXION XXL

EAN CODE: **8714692326981**
SKU CODE: **LB71703871DTXLA00**
ECE NUMBER: **E4-106R-001101**



Recommended rim width:	DW23B
Permitted rim width:	DW25B
Nominal Tyre Pressure:	240 kpa
Section Width:	730 mm
Outer Diameter:	1930 mm
Static Loaded Radius:	870 mm
Rolling Circumference:	5760 mm
SRI:	925
Tread depth:	58 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10C	4955	5625	6315	6990	7675	8220	8695	9215	9600	9935	10340	10455
10L	4370	4965	5570	6165	6770	7255	7670	8130	8470	8765	9120	9225
10H	3630	4210	4785	5355	5755	6095	6430	6705	6945	7070		
25	3740	4340	4935	5520	5930	6280	6625	6910	7155	7290		
30	3630	4210	4785	5355	5755	6095	6430	6705	6945	7070		
40		4010	4560	5100	5480	5805	6120	6385	6610	6735		
50		3845	4370	4890	5255	5565	5870	6125	6340	6460		
65			4160	4660	5005	5300	5590	5830	6040	6150		
70			3790	4240	4555	4825	5085	5305	5495	5595		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES