

# 710/70 R 42 173D TL TRAXION XXL

EAN CODE: **8714692326998**  
SKU CODE: **LB71704273DTXLA00**  
ECE NUMBER: **E4-106R-001102**



|                        |                |
|------------------------|----------------|
| Recommended rim width: | <b>DW23B</b>   |
| Permitted rim width:   | <b>DW25B</b>   |
| Nominal Tyre Pressure: | <b>240 kpa</b> |
| Section Width:         | <b>730 mm</b>  |
| Outer Diameter:        | <b>2060 mm</b> |
| Static Loaded Radius:  | <b>940 mm</b>  |
| Rolling Circumference: | <b>6140 mm</b> |
| SRI:                   | <b>975</b>     |
| Tread depth:           | <b>58 mm</b>   |

| Speed<br>(km/h) | Pressure (bar) |      |      |      |      |      |      |      |       |       |       |       |
|-----------------|----------------|------|------|------|------|------|------|------|-------|-------|-------|-------|
|                 | 0,60           | 0,80 | 1,00 | 1,20 | 1,40 | 1,60 | 1,80 | 2,00 | 2,20  | 2,40  | 2,60  | 2,80  |
| 10C             | 5180           | 5880 | 6605 | 7310 | 8025 | 8595 | 9090 | 9635 | 10040 | 10390 | 10810 | 11050 |
| 10L             | 4575           | 5190 | 5825 | 6450 | 7080 | 7585 | 8020 | 8500 | 8860  | 9165  | 9540  | 9750  |
| 10H             | 3795           | 4405 | 5005 | 5600 | 6015 | 6440 | 6720 | 7015 | 7260  | 7475  |       |       |
| 25              | 3910           | 4540 | 5160 | 5775 | 6200 | 6635 | 6925 | 7225 | 7485  | 7705  |       |       |
| 30              | 3795           | 4405 | 5005 | 5600 | 6015 | 6440 | 6720 | 7015 | 7260  | 7475  |       |       |
| 40              |                | 4195 | 4765 | 5335 | 5730 | 6130 | 6400 | 6680 | 6915  | 7120  |       |       |
| 50              |                | 4020 | 4570 | 5115 | 5495 | 5880 | 6140 | 6405 | 6630  | 6825  |       |       |
| 65              |                |      | 4355 | 4870 | 5230 | 5600 | 5845 | 6100 | 6315  | 6500  |       |       |
| 70              |                |      | 3960 | 4435 | 4760 | 5095 | 5320 | 5550 | 5745  | 5915  |       |       |

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

**VREDESTEIN**  
TYRES