

710/75 R 42 175D TL TRAXION XXL

EAN CODE: **8714692244520**
SKU CODE: **LB71754275DTXLA00**
ECE NUMBER: **E4-106R-000443**



Recommended rim width:	DW23B
Permitted rim width:	DW25B
Nominal Tyre Pressure:	240 kpa
Section Width:	735 mm
Outer Diameter:	2150 mm
Static Loaded Radius:	980 mm
Rolling Circumference:	6395 mm
SRI:	1000
Tread depth:	58 mm

Speed (km/h)	Pressure (bar)											
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80
10C	5510	6250	7020	7765	8530	9135	9660	10240	10670	11045	11490	11730
10L	4860	5515	6190	6855	7525	8060	8525	9035	9415	9745	10140	10350
10H	4035	4680	5320	5955	6395	6900	7145	7455	7720	7935		
25	4155	4825	5485	6135	6590	7110	7360	7680	7955	8175		
30	4035	4680	5320	5955	6395	6900	7145	7455	7720	7935		
40		4455	5065	5670	6090	6570	6805	7095	7350	7555		
50		4275	4860	5435	5840	6300	6525	6805	7045	7245		
65			4625	5180	5560	6000	6215	6480	6710	6900		
70			4210	4710	5060	5460	5655	5900	6110	6280		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10C: Cyclic field activities at low torque up to 10 km/h where the maximum load per tyre fluctuates greatly and where the maximum load is carried not more than 1500 meter. For slopes of over 10% up to 20% increase the inflation pressure with 0,5 bar. For slopes over 20% only the basic load capacity applies.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.

VREDESTEIN
TYRES