

# 800/65 R 32 167A8/B TL TRAXION XXL

EAN CODE: **8714692206306**  
SKU CODE: **LB806532678TXLA00**  
ECE NUMBER: **E4-106R-000437**



Recommended rim width:	<b>DW27B</b>
Permitted rim width:	<b>DW25B</b>
Nominal Tyre Pressure:	<b>160 kpa</b>
Section Width:	<b>825 mm</b>
Outer Diameter:	<b>1840 mm</b>
Static Loaded Radius:	<b>845 mm</b>
Rolling Circumference:	<b>5490 mm</b>
SRI:	<b>875</b>
Tread depth:	<b>54 mm</b>

Speed (km/h)	Pressure (bar)							
	0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00
10L	4455	5050	5670	6270	6890	7370	7775	8255
10H	3435	3985	4530	4995	5395	5830		
25	3565	4135	4700	5185	5595	6050		
30	3435	3985	4530	4995	5395	5830		
40		3725	4235	4670	5040	5450		
50		3725	4235	4670	5040	5450		

- The dimensions indicated, which apply to a nominal tyre pressure, may vary in practice under the influence of actual tyre pressure and conditions of use.
- These specifications may be subject to change without notice. No liability accepted for errors or misprints.
- It is recommended not to exceed the maximum tyre pressures shown in the tables.
- For intensive transport activities at more than 30 km/h, the tyre pressure should be increased by 0,4 bar.
- When working on slopes over 20%, the tyre pressure should be increased by 0,4 bar.
- 10L: Activities where low torque is required at maximum 10 km/h.
- 10H: Field activities where high torque is required at maximum 10 km/h.